

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TE PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TE INCORPORATED, HARRISBURG, PA.

THIS DRAWING IS A CONTROLLED DOCUMENT FOR
TE INCORPORATED. IT IS SUBJECT TO CHANGE
AND THE CONTROLLING ENGINEERING ORGANIZATION
SHOULD BE CONTACTED FOR THE LATEST REVISION



- 1-829 155-6 AS SHOWN
WIE GEZEICHNET

CUTTING TABLE

 CRITICAL INSPECTION DIMENSIONS kritische Kontrollmasse	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: n. ISO 8015 n. ISO 2768 - mH - E n. DIN 16901 - 120
 	0 PLC $\pm 0,1$ 1 PLC $\pm 0,1$ 2 PLC $\pm 0,1$ 3 PLC $\pm$ 4 PLC $\pm$
ANGLES: -	
SURFACE TEXTURE 	

OWN	22.12.88	MATERIAL	HEAT TREAT
COBAN		-	-
CHK	02.01.89		-
R.KRÄMER			
APVD	-		TE Connectivity
-			
NAME 2-16 POS. AMP-QUICK PIN HEADER, 90°, GOLD PLATED 2-16 POL. AMP-QUICK STIFTLISTE, 90°, VERGOLDET			
SCALE	SIZE	DRAWING NO	SHEET
5:1	A2	829155	1 OF 1
			C4