


7		6		5		4		3		2		1							
SOLID CONTACT PART NUMBER 		SIZE TYPE	WIRE SIZE AWG [mm ²]	REF. ONLY CRIMP TENSILE LBS [N]	RECOMMENDED STRIP LENGTH INCH [mm]	CONTACT IDENTIFICATION INFO & NOTES		REV M	HDT-48-00	REVISIONS									
								SYM	DESCRIPTION	DATE	APPROVED								
0460-204-12** 0460-211-12** 0460-220-12** 0460-235-12** 0460-258-12** 0462-203-12** 0462-210-12** 0462-214-12** 0462-215-12**	12 PIN	12 AWG	3.0 mm ² 2.5 mm ²	75 [334]	.222-.284 [5.64-7.21]	0462-215-12** MARKING 1 GRAY BAND, NARROW 1 BROWN BAND, NARROW 1 BROWN BAND, BROAD		J	REVISED PER E.O. P19922	6-25-08	R.D.R.								
		12 PIN						K	REVISED PER E.O. P20130	2-3-09	R.D.R.								
		12 PIN						L	REVISED PER E.O. P20837	3-9-11	R.D.R.								
		12 SOC	70 [311]					M	REVISED PER E.O. P21299	4/13/12	DM								
		12 SOC																	
		12 SOC																	
		0460-256-12**	12 PIN	1.5 mm ² 16 AWG 1.0 mm ²				35 [156]	25 [111]	.222-.284 [5.64-7.21]									
				18 AWG 0.75 mm ²															
		0460-215-16** 0462-209-16**	16 PIN 16 SOC	14 AWG 2.0 mm ²				70 [311]		.250-.312 [6.35-7.92]	1 GREEN BAND, BROAD 1 GREEN BAND, BROAD								
0460-002-16** 0460-202-16** 0460-211-16** 0460-230-16** 0460-235-16** 0460-247-16** 0462-004-16** 0462-007-16** 0462-201-16** 0462-214-16** 0462-221-16** 0462-222-16**	16 PIN 16 PIN 16 PIN 16 PIN 16 PIN 16 PIN 16 SOC 16 SOC 16 SOC 16 SOC 16 SOC 16 SOC	1.5 mm ² 16 AWG 1.0 mm ²	35 [156]	25 [111]	.250-.312 [6.35-7.92]	0460-002-1631 AND 0462-004-1631 MARKING 1 BLUE BAND, BROAD													
		18 AWG 0.75 mm ²																	
		20 AWG 0.50 mm ²																	
		16 AWG 1.0 mm ²	35 [156]	20 [89]	.250-.312 [6.35-7.92]	1 BLUE BAND, NARROW													
		1.5 mm ² 16 AWG 1.0 mm ²																	
		16 AWG 1.0 mm ²	35 [156]	20 [89]	.117-.237 [4.49-6.02]	USE 2.0 mm ² DIAL SET													
		1.5 mm ² 16 AWG 1.0 mm ²																	
		16 AWG 1.0 mm ²	20 [89]	10 [44]	.156-.218 [3.96-5.54]	1 PURPLE BAND, BROAD													
		1.00 mm ² 18 AWG 0.75 mm ²																	
		20 AWG 0.50 mm ²	20 [89]	10 [44]	.156-.218 [3.96-5.54]	SLOTTED (SPLIT) PIN  													
		22 AWG 0.35 mm ²																	
112349 112352	12 PIN 12 SOC	12 AWG 3.0 mm ² 2.5 mm ²	75 [334]		.222-.284 [5.64-7.21]	SLOTTED (SPLIT) PIN  													
		14 AWG 2.0 mm ²	70 [311]																
0460-201-1690 0461-201-1690	16 PIN 16 SOC	1.5 mm ² 16 AWG 1.0 mm ²	35 [156]		.222-.284 [5.64-7.21]	SLOTTED (SPLIT) PIN													
		18 AWG 0.75 mm ²	25 [111]																
8960-025-12603 8962-014-12603	12 PIN 12 SOC	4.0 mm ² 12 AWG 3.0 mm ² 2.5 mm ²	75 [334]		.222-.284 [5.64-7.21]														
8960-020-16603 8962-011-16603	16 PIN 16 SOC	1.5 mm ² 16 AWG 1.0 mm ²	35 [156]		.250-.312 [6.35-7.92]														
		18 AWG 0.75 mm ²	25 [111]																
		20 AWG 0.50 mm ²	20 [89]																
 DEPTH ADJUSTING SCREW P/N 0426-209-0000 INCLUDES JAM NUT.																			
 USE 2.5/14 SETTING FOR THIS PART WITH 12 AWG.																			
 USE 1.5 SETTING FOR THIS PART WITH 14 AWG.																			
 CAUTION: NEVER CLOSE TOOL ON GAGE G454. CLOSE TOOL FIRST AND THEN INSERT GAGE.																			
 USE  IN DIAL POSITION  TO CHECK WEAR ANNUALLY. CHECK OFTEN IF USED FOR FREQUENT CRIMPING.																			
NOTES: UNLESS OTHERWISE SPECIFIED																			