


enclosures: **size "49.16"**

**standard** ..... page: 162 ÷ 163  
**aggressive environments** page: 164  
**EMC** ..... page: 165


panel supports:  
**COB + adaptor** ..... page: 258 ÷ 260

- features according to EN 61984:  
**16A 250V 4kV 3**  
 - UL, CSA, CCC, GL certified  
 - for maximum current load, see the insert load curve section on page 30

**inserts,  
 screw terminal connection**



**inserts,  
 screw terminal connection**



description

part No.

part No.


indirect, with plate <sup>1)</sup>  
 female inserts with female contacts  
 male inserts with male contacts

**CDAF 10  
 CDAM 10**


direct, without plate <sup>2)</sup>  
 female inserts with female contacts  
 male inserts with male contacts

**CDAF 10 X  
 CDAM 10 X**


<sup>1)</sup> for non-prepared conductors





dimensions in mm




dimensions in mm




<sup>2)</sup> for conductors with bush terminal



contacts side (front view)



contacts side (front view)



- inserts with plate for section conductors:  
 0.75 ÷ 2.5 mm<sup>2</sup> - AWG 18 ÷ 14  
 - torsion couple recommended for conductor fastening  
 screws and stripping length see section feature of  
 inserts on page 13

- inserts without plate for section prepared conductors:  
 0.25 ÷ 2.5 mm<sup>2</sup> - AWG 24 ÷ 14  
 - torsion couple recommended for conductor fastening  
 screws see section feature of inserts on page 13

dimensions indicated are not binding  
 and may be changed without notice

CDA