







LOC		DIST		REVISONS			
CM	00	P	LTR	DESCRIPTION		DATE	DWN
		A1		REVISED PER ECO-11-005294		30APR11	RK

1. APPLICABLE CONTACT P/N: 170539, 170360, 170361, 170362.
2. DIMENSIONS IN BRACKETS ARE IN INCHES.
- 3 RECOMMENDED PANEL THICKNESS TO BE 0.8-2.0 [.031-.079].
- 4 HOUSING INSERTION INTO THE PANEL CUT OUT MUST BE IN THE SAME DIRECTION AS THE PUNCH.)



RECOMMENDED PANEL CUT OUT
SCALE 4:1



DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN R. WHITAKER 23-JULY-2001		TE Connectivity	
mm[INCHES]		9 PLC ±		CHK C. JONES 23-JULY-2001		NAME	
1 PLC ±		2 PLC ±0.13 [.005]		APVD C. JONES 23-JULY-2001		CAP.	
3 PLC ±		4 PLC ±		PRODUCT SPEC		4 CIRCUIT, SEALED APPLICATION,	
4 PLC ±		ANGLES ±0°10'		APPLICATION SPEC		MINI UNIVERSAL MATE-N-LOK™	
FINISH		WEIGHT		SIZE		RESTRICTED TO	
MATERIAL NYLON UL94V-0 NATURAL		CUSTOMER DRAWING		A 00779 C-794939		-	
				SCALE 5:1		SHEET 1 OF 1	
						REV A1	

794939-1
PART NUMBER