

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

MATED WITH
PASSEND ZU
HA 16

COPYRIGHT - By -

ALL RIGHTS RESERVED.

PROJEKT NR.:

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D6	ECR-17-009069	09FEB2018	SG	MKO

SCREW TERMINATION 4 M3x10.5

CRIMP TERMINATION 5 M3x10.5

SPRING CLAMP TERMINATION 6 M3x10.5

Contact arrangement / view from termination side

Contact arrangement / view from termination side

Contact arrangement / view from termination side

Contact arrangement / view from termination side

NOTES:

1 SUITABLE CRIMP CONTACTS: SERIES HE/HA
OUTER DIMENSIONS OF INSULATION: MAX. ϕ 3,2 MM

⚠ SUITABLE HOOD SIZE 5; 7; 9; 11: SERIES HA; HD
SUITABLE INSERTION AND EXTRACTION TOOL:
SCREWDRIVER 0,5x3 DIN 5264

⚠ Strip lenght: Screw conection 10mm
Spring clamp conection 10mm Crimp conection 7.5mm

⚠ STANDARDS:
DIN EN 61984; DIN EN 60664-1

⚠ PACKAGING:
5 SETS IN A CARTON, PRE-MOUNTED

⚠ SPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 300 PIECES

⚠ SPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 150 PIECES

⚠ SPECIAL PACKAGING: AIS
PACKAGING UNIT: 250 PIECES

⚠ SPECIAL PACKAGING: WIELAND
PACKAGING UNIT: 100 PIECES

⊠ SEE TE CONNECTIVITY QUALITYMANAGEMENT PROCEDURE NO. 1.12

Panel cut-out for contact insert

when used without housing

Assembling instruction

⚠ DISTANCE FOR SAFETY
CONTACT MARKING MAX. 24 mm

1-3	1-2	1-0	0-4	0-7	0-6	0-5	2-9	1-9	7-9	7-8	1-8	2-8	1-7	7-2	7-1	2-3	1-1	DESCRIPTION / BENENNUNG	MATERIAL	COLOR / FARBE	ITEM NO. POS.	REMARKS / BEMERKUNGEN			
																		Pin insert screw	PBT	light beige	8	with stainless steel-fixing screw			
																		Pin insert screw	PBT	light beige	7	with stainless steel-fixing screw			
																		Pin insert screw	PBT	light beige	6	with AU contact			
																		Cover	PBT	light beige	5				
																		Cover	PBT	light beige	4				
																		Cover	PBT	light beige	3				
																		pin insert spring clamp	PBT	light beige	2				
																		pin insert crimp/screw	PBT	light beige	1				
HA-16-Sti.S-B1-16-WIE	HA-16-Sti.S-B1-16-AIS	HA-16-Sti.S-B17-32-KM	HA-16-Sti.S-B1-16-KM	HA-16-Sti.S-VA-B1-16	HA-16-Sti.S-VA-B17-32	HA-16-Sti.S-AU-B1-16	HA-16-Sti.C-B-49-64	HA-16-Sti.S-B-49-64	HA-16-Sti.S-C-B-49-64	HA-16-Sti.S-C-B-33-48	HA-16-Sti.S-B-33-48	HA-16-Sti.C-B-33-48	HA-16-Sti.S-B-17-32	HA-16-Sti.S-C-B-17-32	HA-16-Sti.S-C-B-1-16	HA-16-Sti.C-B-1-16	HA-16-Sti.S-B-1-16								
THIS DRAWING IS A CONTROLLED DOCUMENT.																		DWN	Schneider	09.02.2000					
																		CHK	Schweiger	09.02.2000					
																		APVD							
																		PRODUCT SPEC		108-74007		NAME		Male insert HA.16.Sti.C	
																		APPLICATION SPEC		114-77009		DRAWING NO		C=1103416	
																		WEIGHT		A2		CAGE CODE		00779	
																		CUSTOMER DRAWING		SCALE		SHEET		1 OF 1	
																				1:1		REV		D6	

1471-9 (1/15)

1103416

A