

# LANGOFLEX PET V0


- ▶ Mechanical and abrasion protection
- ▶ Non-flammable

- ▶ mechanischer Schutz und Abriebschutz
- ▶ nicht brennbar



- **Product family:** Expandable Sleeving
- **Construction:** UL94 V0 PET .010" (0.25mm) braided monofilament
- **Temperature of use:** -40/150°C
- **Standard colors:** black
- **Cutting:** hot cutting
- **Packaging:** spools, cut lengths upon request
- **Typical applications:**
  - Lighting fixtures
  - Transportation
  - Industrial equipment

- **Produktfamilie:** Aufdehnbare Schläuche
- **Konstruktion:** UL 94 V0-PET-Monofilamentgeflecht .010" (0.25 mm)
- **Betriebstemperatur:** -40/150°C
- **Standardfarbe:** schwarz
- **Schnitt:** Heißschnitt
- **Lieferformen:** Spulen, Schnittlängen auf Anfrage
- **Typische Anwendungen:**
  - Beleuchtungskörper
  - Transport
  - Industrieanlagen



Schlemmer Part no. on page:  
Schlemmer Artikelnr. auf Seite:  
82



EN 45 545-2

Designation Beschreibung	Nominal A Ø (mm) Nominal A Ø (mm)	Maximum B Ø (mm) Maximal B Ø (mm)
LANGOFLEX PET V0 03	3	6
LANGOFLEX PET V0 05	5	9
LANGOFLEX PET V0 06	6	9
LANGOFLEX PET V0 08	8	11
LANGOFLEX PET V0 10	10	13
LANGOFLEX PET V0 12	12	17
LANGOFLEX PET V0 14	14	22
LANGOFLEX PET V0 16	16	25
LANGOFLEX PET V0 20	20	27
LANGOFLEX PET V0 25	25	34
LANGOFLEX PET V0 40	40	51